

Statement of Evidence:

L011

The North Quarter Corner of Section 1, Township 36 North, Range 30 West, Minden Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

10" Elm	N 12 E	9 links
6" Ironwood	S 20 W	17 links

1939 County Engineer's Notebook No. 127 contains survey of CAR 29 running west to east on section line. Corner is shown as a spike set in center of road in line with fence north. Ties:

Cor. FP	S	37.5'
FP	SE	46.2'

Stationing gives distances of 2700.0 feet to the NE corner and 2669.9 feet to the NW corner with a delta angle of 0-48' left.

2002 No resurvey information was found on this corner in the Benton County Surveyor's records.

2004 Westwood Professional Services found a CIM and measured 2697.51 feet to the NE corner and 2672.42 feet to the NW corner.

County Coordinates Obtained by GPS to CIM
NAD 83 (1996 Adjustment)
N- 132140.762
E- 507885.405

2009 Westwood Professional Services, Inc. found a CIM in the same coordinate position that was reported in 2004. The CIM is located in the center of Co. Rd. 44 on a fence line to the north and recessed below the bituminous surface. A PK nail with Benton County disk was placed over the CIM and reference ties were established.