

**Statement of Evidence:**

**L081**

The North Quarter Corner of Section 8, Township 36 North, Range 30 West, Minden Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey set a wood post at the corner location and bearing trees were recorded.  
6" Blk Oak                    N 5 3/4 E                    1576 links

1933 County Engineer's Notebook No. 71 contains survey of County road running west to east. Notes show corner marked by a hub and rock in center of road. Ties:  
F.P.    NE    52.0'  
T.P.    NW    55.9'  
Stationing gives distances of 2675.2 feet to the NE corner and 2638.3 feet to the NW corner with a delta angle of 0-40' right.

1933 County Engineer's Notebook No. 71 contains survey of Township road running south to north. Notes show corner marked by a hub and rock in center of road intersection.

1957 County Surveyor's Record Book 1, page 175, notes the following reference ties to a hub and rock at the corner:  
TP    SE    115.4  
TP    SW    48.7

1962 Carley Engineering survey notes give distance of 5319.64 feet between section corners with corner set midway and on line.

1992 Paul Wollen, LS 10461, found a RR spike at the intersection of the centerlines north/south and east/west. He replaced it with a cast iron monument and filed a Certificate of Location (#216300).

2002 Found CIM with approximate distance to the NW corner being 2642 feet.  
County Coordinates obtained by traverse to CIM.  
NAD 83 (1996 Adjustment)  
N- 126691.726  
E- 486745.679

2004 Information from BWK gives distance of 2676.84 feet to the NE corner.

2007 Westwood Professional Services, Inc. excavated the corner location. A 1/2" iron pipe capped 19552 was placed over a found red granite stone. The monument location fits centerline of north-south and east-west roads. New reference ties were created.  
County Coordinates obtained by GPS  
NAD 83 (1996 Adjustment)  
N- 126693.678  
E- 486746.368