

**Statement of Evidence:**

**L091**

The North Quarter Corner of Section 9, Township 36 North, Range 30 West, Minden Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey set a wood post at the corner location and bearing trees were recorded.

|            |            |          |
|------------|------------|----------|
| 6" Blk Oak | N 58 E     | 50 links |
| 6" Blk Oak | S 40 3/4 E | 66 links |

1933 County Engineer's Notebook No. 71 contains survey of County road running west to east. Notes show corner marked by a hub set in center of road with fence line north. Ties:

|            |    |       |
|------------|----|-------|
| Cor. F.P.  | N  | 28.3' |
| 10" R. Oak | NW | 50.3' |

Stationing gives distances of 2666.8 feet to the NE corner and 2648.7 feet to the NW corner with a delta angle of 0-20' right.

1964 County Surveyor's Record Book 1, page 177, notes the following reference ties to an iron:

|           |     |       |
|-----------|-----|-------|
| 24" R Oak | WNW | 100.0 |
| 30" R Oak | WNW | 108.8 |

1982 David Regan, LS 12236, found a 1/2" solid iron pin in the centerline of east/west road and in a fence line north. He set a cast iron monument over the iron and filed a Certificate of Location (#162590). Fits 1964 ties.

2004 County Coordinates obtained from GPS by BWK to CIM:

NAD 83 (1996 Adjustment)

N- 126812.374

E- 492072.190

Distances:      2664.11 feet to the NE corner  
                    2651.03 feet to the NW corner  
                    delta = 0-18'-43" right

2008 Westwood Professional Services, Inc. found a CIM at the centerline of east/west bituminous road, and fence line north.

County Coordinates obtained by GPS

NAD 83 (1996 Adjustment)

N- 126812.374

E- 492072.190