

Statement of Evidence:

L101

The North Quarter Corner of Section 10, Township 36 North, Range 30 West, Minden Township, 4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey set a wood post at the corner location and bearing trees were recorded.

8" Bur Oak	S 15 1/2 E	120 links
8" Bur Oak	S 73 1/2 W	440 links

1933 County Engineer's Notebook No. 71 contains survey of County road running west to east. Notes show corner marked by a 2" x 3" x 12" stone in center of road with fence line south. Ties:

Twin R. Oak South 40.5'
10" R. Oak SW 76.0'

Stationing gives distances of 2634.8 feet to the NE corner and 2637.5 feet to the NW corner with a delta angle of 0-06' left.

1964 County Surveyor's Record Book 1, page 179 notes the following reference ties to an iron:

16" Oak	SW	134.3
12" Oak	SW	68.55
3 rd FP	S	46.65

1989 David Regan, LS 12236, set a cast iron monument in the centerline of County Road 44 on a fence line south, using one Benton County tie. He filed a Certificate of Location (#195018).

2008 Westwood Professional Services, Inc. found a CIM at centerline of east/west road, and fence line south. Established new reference ties.

County Coordinates obtained by GPS
NAD 83 (1996 Adjustment)
N-126793.692
E-497373.195

Note: Need to check for stone!