

Statement of Evidence:

L151

The North Quarter Corner of Section 15, Township 36 North, Range 30 West, Minden Township, 4th Principal Meridian, Benton County, Minnesota.

1852 Original General Land Office survey established this corner and a wood post was set for the corner and bearing trees were recorded.

8" Bur Oak	N 87 1/2 E	177 links
8" Bur Oak	S 77 3/4 E	126 links

1971 William Lunser, LS 9394, notes a distance of 2651.66 feet to the NE Cor (3/4" I.P.) per Doc. No. 133424. County Surveyor's Record Book 1, page 189, notes a distance of 2651.66 feet to the NE corner Sec 15 and a distance of 2652.75 feet to the NW corner Sec 15. This information is from Lunser and he notes a set 1/2" I.P. at a fence corner.

2004 Found 1/2 " iron pipe with cap No. 9394 and measured 2651.86 feet to iron pipe at NE corner and 2653.40 to CIM at the NW corner.
County Coordinates obtained by GPS to iron pipe:
NAD 83 (1996 Adjustment)
N- 121475.920
E- 497433.906

2009 Found 1/2 " iron pipe with cap No. 9394 and measured 2651.86 feet to iron pipe at NE corner and 2653.40 to CIM at the NW corner. The 2004 coordinates were verified and reference ties were established. Corner position appears to fit well with occupation lines in the vicinity and is accepted as the best available evidence for the corner.