

Statement of Evidence:

L211

North Quarter Corner of Section 21, Township 36 North, Range 30 West, Minden Township, 4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

6" Bur Oak	S 33 E	69 links
6" Bur Oak	N 75 E	75 links

1992 County Coordinates from MN/DOT to iron pipe:

NAD 83 (1986 Adjustment)
N-116080.476
E-492158.527

2001 Westwood Professional Services, Inc. found a 1/2" iron monument at the intersection of the centerline of County Road 80 and fence line from the north. Removed iron monument and set a cast iron monument at the location and established new reference ties.

2002 No resurvey information was found on this corner in the Benton County records.

2003 Measured 2672.06 feet to the NW corner and 2667.88 feet to the NE corner and found the CIM to be on line between section corners.
County Coordinates obtained by GPS to CIM:
NAD 83 (1996 Adjustment)
N- 116081.079
E- 492158.038

2009 Westwood Professional Services recovered a Cast Iron Monument 1.5 feet south of the road centerline and on line with a field line to the north. Reference ties were established.

2012 Since the CIM fits the lost position between section corners within 2 feet, it is accepted as the best available evidence of the corner position.