

**Statement of Evidence:**

**L251**

The North Quarter Corner of Section 25, Township 36 North, Range 30 West, Minden Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1852 Original General Land Office survey established this corner set a wood post at this location and bearing trees were recorded.  
12" Bur Oak N 81 W 175 links

1924 County Engineer's Notebook No. 50 shows survey by H. G. Elletson of SR No. 95 running from east to west with job ending at this corner. Corner is shown as a bolt. Stationing gives distance of 2649.7 feet to the NE corner. Ties:  
F.P. NE 56.1'  
TP SE 37.3'

1937 County Engineer's Notebook No. 106 notes corner as a spike in the center of State Hwy. 95. Road survey run south with ties:  
F.P. N 32.45  
TP NW 35.6

No Date County Surveyor's Record Book 1, page 5, notes on a road alignment survey that a stake/post marked this corner location.

1942 Minnesota Highway Department notes (Book 89, pages 1-26) call for a 60d spike at the intersection of roads east/west/south and a fence line north. The spike was replaced with a wood hub.

1949 On November 9, 1949 C.H. West, LS 932, found a 2" X 2" wood hub. He placed a 8" X 30" round pre-cast concrete monument with a cap at the corner and established 2 reference monuments. This is also noted in the Minnesota Highway Department notes in Book 91, pages 1-24. He filed a certificate in 1951.

1988 On November 29, 1988 William Lunser, LS 9394, found a Highway Department monument and set cast iron monument over it. He notes a distance of 2649.67 feet to the NE corner Sec 25. He filed a Certificate of Location.

1997 On July 7, 1997 James Nielsen, LS 11865, found a cast iron monument with concrete below it as shown on Certificate of Location (#261570). He also found and checked Lunser's ties. Corner is 15.2 feet north of the centerline of TH 95.

2008 Westwood Professional Services, Inc. placed a PK nail and county washer over a found CIM. Established reference ties.  
County Coordinates obtained by GPS  
NAD 83 (1996 Adjustment)  
N-110632.980  
E-508183.331