

Statement of Evidence:

G191

North Quarter Corner of Section 19, Township 37 North, Range 30 West, 4th Principal Meridian, Mayhew Lake Township, Benton County, Minnesota.

1852 Original US General Land Office survey established corner marked by a wood post with bearing trees noted as.

24" Blk Oak	S 35 1/2 W	50 links
8" Blk Oak	N 65 1/2 W	150 links

1879 County Surveyor's Record Book 1, page 233, notes that Richard Cronk did a road survey from this corner and he notes a post at the corner.

1979 Paul Wollen, LS 10461, found a 1" iron pipe at intersection of fence lines north and west. He replaced it with cast iron monument and filed a Certificate of Location (#154383). Notes show he measured 2825.25 feet to the NW corner.

2006 Westwood Professional Services Inc. found a cast iron monument on the east side of a corner fence post and on line with distant tree line to the east. Distances measure 75 feet of GLO west and 112 feet long of GLO to the east. The closing distances along the north and west tier of sections in the townships of Benton County typically measure long of GLO distance. The CIM is accepted as marking the corner position.

Coordinates Obtained by GPS
NAD 83 (1996 Adjustment)
N-148166.948
E-481553.256

2009 Westwood Professional services found the CIM, established reference ties and verified the 2006 coordinates.