

**Statement of Evidence:**

**L022**

The Northeast Corner of Section 2, Township 36 North, Range 30 West, Minden Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey established this corner and note a wood post was set with bearing trees marked.

12" Elm	N 84 E	30 links
18" Elm	N 35 W	28 links
8" Elm	S 48 W	119 links
16" Elm	S 72 E	25 links

1939 County Engineer's Notebook No. 127 contains survey of CAR 29 running west to east on section line. Corner is shown as an iron pipe in center of road in line with fences north and south. Ties:

FP	NW	39.55
FP	NE	38.15

1961-1968 The following reference ties are noted in County Highway records.

PP	S	28.73
24" Elm	S	99.13
Cor FP	N	31.38

1995 Kevin Festler, LS 22702, found a 1 1/2" pipe at the intersection of the centerline of County Road 44 and a fence line north. A Certificate of Location (#230315) was filed.

Comstock and Davis performed GPS work under contract with Benton County.

County Coordinates Obtained by GPS NAD 83 (1986 Adjustment) to a 1 1/2" iron pipe:  
N- 132195.406  
E- 505214.046

2008 Westwood Professional Services, Inc. found a 1 1/2" iron pipe fitting centerline of County Rd. 44 (east/west road). Established reference ties.

County Coordinates Obtained by GPS  
NAD 83 (1986 Adjustment)  
N- 132195.508  
E- 505213.549