

**Statement of Evidence:**

**L042**

The Northeast Corner of Section 4, Township 36 North, Range 30 West, Minden Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey established this corner and set a wood post and marked bearing trees:

8" Blk Oak	S 47 W	134 links
2" Blk Oak	N 3 E	37 links

1890 County Road Book, page 32, contains Surveyor's Report by Felix Parrent stating road laid out on section lines south and east from this corner.

1989 David Regan, LS 12236, searched and dug in the area of the corner and found nothing. He set a cast iron monument using a section subdivision of Section 3. A Certificate of Location (#195016) was filed. He notes a distance of 2674.17 feet to the North ¼ corner of Section 3.

1995 Comstock and Davis performed GPS work under contract with Benton County and Coordinates Obtained by GPS NAD 83 (1986 Adjustment) to a CIM:  
N- 132257.229  
E- 494577.667

2001 William Lunser, LS 9394, notes per Doc. No. 283105 a distance of 2642.22 feet to the East ¼ corner of Section 33 of Mayhew Lake Township.

2007 Westwood Professional Services, Inc. found a CIM at centerline 55<sup>th</sup> St. NE and established reference ties. The CIM fits Mr. Regan's distance east within 0.07 feet and Mr. Lunser's distance north within 0.22 feet.

County Coordinates  
NAD 83 (1996 Adjustment)  
N-132257.350  
E-494577.114