

Statement of Evidence:

L052

The Northeast Corner of Section 5, Township 36 North, Range 30 West, Minden Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey established this corner and note a wood post was set with bearing trees marked:

6" Blk Oak	N 40 E	26 links
4" Blk Oak	N 64 W	24 links

1933 County Engineer's Notebook No. 71 contains survey of Township road running south to north and terminating at or near this corner. Notes show possible corner marked by a hub in center of road east. Ties:

R. Oak	E	26.7'
Twin Maple	S	33.8'

1957 M.W.Carley notes the following reference ties to an iron monument. (Also noted in the County Surveyor's Record Book 1, page 169.)

12" Oak	SE	111.1
12" Oak	SW	108.5
12" W Oak	SE	97.6
PP	SW	50.7

1961-1968 MW Carley notes the following reference ties.

Trans. Pole		50.3
Tele. Pole	NW	38.64
16" Oak	SE	97.55

1995 Kevin Festler, LS, set a 1/2" pipe, capped #16097, at the intersection of the centerline of an east/west road, fence line south and 2 ties from 1961. He filed a Certificate of Location (#230316). Comstock and Davis performed GPS work under contract with Benton County and County Coordinates Obtained by GPS: NAD 83 (1986 Adjustment) to an iron pipe:

N-132202.112
E- 489275.291

2008 Westwood Professional Services, Inc. found a 1/2" iron pipe (cap destroyed) at the centerline of east/west road, and fence line south.

County Coordinates obtained by GPS
NAD 83 (1996 Adjustment)
N-132202.267
E-489274.712