

**Statement of Evidence:**

Northeast Corner of Section 8, Township 36 North, Range 30 West, Minden Township,  
4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1852 Original General Land Office survey established this corner and a wood post was set for the corner and bearing trees were recorded.

10" Bur Oak	S 83 1/2 E	185 links
15" Bur Oak	S 33 1/2 W	206 links

1890 County Road Book, page 32, contains Surveyor's Report by Felix Parrent stating road laid out on section lines south and east from this corner.

1933 County Engineer's Notebook No. 71 contains survey of County road running west to east. Notes show corner marked by a hub in center of road with fence lines north and south. Ties:

F.P.	NE	43.6'
T.P.	S	30.0'

Stationing gives delta angle of 0-04' left with a note that made point a POT later.

1964 County Surveyor's Record Book 1, page 167, notes the following reference ties to an iron:

PP	NW	34.5
FP	NW	39.05

This corner is 2652 feet from the East 1/4 corner Sec 5.

1982 David Regan, LS 12236, found a 1/2" solid iron in the centerline of an east/west road and on a fence line north, 13.0 feet west of a driveway south. He set a cast iron monument over the iron and filed a Certificate of Location (#162589).

1995 Comstock and Davis performed GPS work under contract with Benton County and Coordinates Obtained by GPS NAD 83 (1986 Adjustment) to a CIM:

N-	126752.635
E-	489422.325

2004 County Coordinates obtained using GPS by BWK  
NAD 83 (1996 Adjustment)  
N- 126752.814  
E- 489421.825

2008 Westwood Professional Services, Inc. found a CIM at the centerline of east/west bituminous road, and fence line north. Established reference ties to corner.  
County Coordinates obtained using GPS  
NAD 83 (1996 Adjustment)  
N- 126752.814  
E- 489421.825

Benton County Surveyor's Office  
Gary H. Stevenson, County Surveyor  
Minnesota License No. 12684