

Statement of Evidence:

L092

Northeast Corner of Section 9, Township 36 North, Range 30 West, Minden Township,
4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey established this corner and a wood post was set for the corner and bearing trees were recorded.

12" Bur Oak	N 78 3/4 E	126 links
15" Bur Oak	S 55 1/2 E	169 links

1933 County Engineer's Notebook No. 71 contains survey of County road running west to east. Notes show corner marked by a flat rock with "+" in center of road with fence lines north and south. Ties:

10" W. Oak	SE	94.0'
Cor. F.P.	S	28.7'

Stationing gives distances of 2637.5 feet to the N 1/4 corner Sec. 10 and 2666.8 feet to the North 1/4 corner Sec. 9 with a delta angle of 3-27' left.

1962 County Surveyor's Record Book 1, page 177, notes an iron at the corner.

1992 Paul Wollen, LS 10461, found a PK nail and replaced it with a cast iron monument. He filed a Certificate of Location (#216287).

1995 Comstock and Davis performed GPS work under contract with Benton County Coordinates Obtained by GPS NAD 83 (1986 Adjustment) to a CIM:
N- 126886.640
E- 494735.843

2004 County Coordinates obtained using GPS by BWK to CIM:
NAD 83 (1996 Adjustment)
N- 126886.720
E- 494735.265

2008 Westwood Professional Services, Inc. found a CIM at the centerline of east/west 45th St NE, established new reference ties and verified the 2004 coordinates.

2009 Westwood Professional Services, Inc. set a PK nail and washer over the existing found CIM. Reference ties were verified.