

**Statement of Evidence:**

**L112**

Northeast Corner of Section 11, Township 36 North, Range 30 West, Minden Township,  
4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1852 Original General Land Office survey established this corner and a wood post was  
set for the corner and bearing trees were recorded.

12" Elm	N 59 1/4 W	169 links
15" Ash	N 1 E	88 links

1995 Kevin Festler, LS 22702 set a 1/2 " iron pipe (LS 16097) at the intersection of  
fence lines north, south, and east as an obliterated corner and filed a Certificate of  
Location (Doc. 230317).

Comstock and Davis performed GPS work under contract with Benton County  
and Coordinates Obtained by GPS NAD 83 (1986 Adjustment) to the set 1/2 " iron  
pipe:

N- 126527.046  
E- 505323.749

2002 Westwood Professional Services, Inc. found no other record information on this  
corner in the Benton County records.

2004 MN/DOT found 3/4" iron pipe.  
County Coordinates obtained by GPS  
NAD 83 (1996 Adjustment)  
N- 126527.186  
E- 505323.219

2008 Westwood Professional Services, Inc. found a 1/2" iron pipe capped 16097 at a  
north/south fence line. Established reference ties.  
County Coordinates obtained by GPS  
NAD 83 (1996 Adjustment)  
N- 126527.092  
E- 505323.287