

Statement of Evidence:

L142

Northeast Corner of Section 14, Township 36 North, Range 30 West, Minden Township,
4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey established this corner and a wood post
was set for the corner and bearing trees were recorded.

16" Bur Oak	S 15 E	565 links
20" Bur Oak	S 89 3/4 W	600 links

1961 M.W. Carley ties:

Corner FP	N	22.19
TP	NE	37.85
PP	NW	63.15

1995 Kevin Festler, LS 22702 set a ½ " iron pipe (LS 16097) at the intersection of
fence line north and roads west, south, and east as an obliterated corner and filed a
Certificate of Location (Doc. 230320).

Comstock and Davis performed GPS work under contract with Benton County
and Coordinates Obtained by GPS NAD 83 (1986 Adjustment) to a set ½ " iron
pipe:

N- 121204.626
E- 505393.773

1999 William Lunser used corner to set East Quarter corner of Section 14.

Note: 1961 and 1995 do not appear to agree.

2004 County Coordinates obtained by GPS to ½ " iron pipe:

NAD 83 (1996 Adjustment)
N- 121204.944
E- 505393.309

2009 Westwood Professional Services, Inc. found a ½" capped iron pipe (cap
destroyed) fitting PI of curve in bituminous road. The iron pipe is about 26 feet
south of an old down fence line.

The Minnesota Department of Transportation file a Certificate of Location of
Government Corner (Document Number 368987)