

**Statement of Evidence:**

**L162**

The Northeast Corner of Section 16, Township 36 North, Range 30 West, Minden Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1852 Original General Land Office survey established this corner and a wood post was set for the corner and bearing tree was recorded:  
8" Burr Oak      S 80 W      525 links

1913 County Surveyor Record Book, pages 42 and 43, contains a survey in Section 16 by J. A. Stanton. Survey shows corner indicated by fences radiating therefrom, which have been maintained for many years and recognized by adjoining owners. Gives distance of 5222 to the NW corner Section 16.

1935 County Engineer's Notebook No. 87 contains a survey for SAR No 3 and No. 4 running from Foley to Sauk Rapids. Survey notes corner as fence corner with fences running west and north being 48.0 feet west of the PI.

1969 RCM ties to a 1/2" I.P.  
P.P.      NW      59.43      G.P.      SW      13.66  
T.P.      SW      8.35

1971 William Lunser, LS 9394, found a 1/2" iron pipe. He left it in place and a Certificate of Location (#133425) was recorded with ties:  
P.P.      SW      13.6      P.P.      NW      59.4  
Cor F.P. W      63.2  
Information gives distances of 2652.75 feet to the North 1/4 corner Sec. 15 and 2657.65 feet to the East 1/4 corner Sec. 16.

1994 Central Minnesota Land Surveying found 3/4" iron pipe at the extension of fence line and centerline of County Road 3. Left as was. Lunser's ties destroyed. Established new tie.  
B.C.H.D in P.P.      NE      89.98

1995 Comstock and Davis performed GPS work under contract with Benton County and Coordinates Obtained by GPS NAD 83 (1986 Adjustment) to a 3/4" iron pipe:  
N- 121540.744  
E- 494781.832

2001 Westwood Professional Services, Inc. found a 1/2" iron monument in road ditch at the extension of centerline of County Road 3 west and tree line from the north. The pipe fit with being 48 feet west of the approximate PI. Removed and set cast iron monument and established new reference ties.

2003 From CIM measured 2653.40 feet to the North 1/4 corner Sec. 15  
County Coordinates obtained by GPS to CIM:  
NAD 83 (1996 Adjustment)  
N- 121540.871  
E- 494781.305  
Corner is accepted as marking the obliterated corner position.

2008 Westwood Professional Services, Inc. found the CIM and established new reference ties.