

Statement of Evidence:

L182

Northeast Corner of Section 18, Township 36 North, Range 30 West, Minden Township,
4th Principal Meridian, Benton County, Minnesota.

1852 Oringinal General Land Office survey established this corner and set a wood post with bearing trees marked.

8" Blk Oak	N 12 1/2 E	913 links
8" Blk Oak	N 22 1/2 W	292 links

1917 County Surveyor's Record Book 1, page 195, R.H. West notes a stone at the corner and a distance of 2635 feet to the East 1/4 corner Sec 7.

1961 In 1961 and 1968, Carley Engineering notes a stone down 2.9 feet at the corner with the following reference ties.

N-end C.M.C.	E	32.60
S-end C.M.C.	SE	37.60
S-end C.M.C.	SW	35.75
N-end C.M.C.	W	27.60

1982 David Regan, LS 12236, found a 1/2" iron pipe over a stone in the centerline of a north/south road and on a fence line east/west. He filed a Certificate of Location (#162592). He set a cast iron monument over the stone and removed the pipe. His ties check well with the 1961 and 1968 ties.

1995 Comstock and Davis performed GPS work under contract with Benton County and Coordinates Obtained by GPS NAD 83 (1986 Adjustment) to a CIM:

N- 121377.110
E- 484133.983

2002 12/16/02, Westwood Professional Services, Inc. found a busted CIM. We measured 2644.45 feet north to the East 1/4 corner of Section 7.
County Coordinates obtained by GPS
NAD 83 (1996 Adjustment)
N- 121377.217
E- 484133.395

2008 Westwood Professional Services, Inc. Established reference ties to a found CIM.
County Coordinates obtained by GPS
NAD 83 (1996 Adjustment)
N- 121377.217
E- 484133.395