

Statement of Evidence:

L242

The Northeast Corner of Section 24, Township 36 North, Range 30 West, Minden Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey established this corner set a wood post at this location and bearing trees were recorded:

6" Blk. Oak	N 64 W	142 links
2" Blk. Oak	S 43 W	379 links

1930 County Engineer's notebook No. 60 for CR 25 running north-south shows a spike at the corner with fence lines running east and west. Same ties as listed in 1938.

1938 County Surveyor's Record Book 1, page 207, H. G. Elletson notes a spike with the following reference ties.

F.P.	E	32.7 feet
F.P.	NE	48.5 feet

1994 Comstock and Davis, Inc. set a cast iron monument at the intersection of the centerline of County Road 25 (running north and south) and fence lines running east and west. A Certificate of Location (#226897) was recorded.

1995 Comstock and Davis performed GPS work under contract with Benton County and Coordinates Obtained by GPS NAD 83 (1986 Adjustment) to a CIM:

N- 116105.236		
E- 510758.633		

2001 Westwood Professional Services, Inc. found a cast iron monument at the intersection of the centerline of County Road 25 (running north and south), which fit with 1994 ties. We found 2 ties from 1994 that fit and made 1 new one:

PK in top CMP	NW	34.00
---------------	----	-------

County Coordinates Obtained by GPS (CIM)
NAD 83 (1996 Adjustment)
N-116105.351
E-510758.188

2008 Westwood Professional Services, Inc. found the CIM and established new reference ties as shown.

2010 The Benton County Surveyor's Office visited the corner position and no remains of the CIM could be found. Also a new CMP was found in the southwest quadrant requiring a new reference tie. The 2001 coordinates were verified.