

Statement of Evidence:

L262

Northeast Corner of Section 26, Township 36 North, Range 30 West, Minden Township,
4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey established this corner and notes show a wood post set at this location and bearing trees were recorded.

3" Blk Oak N 55 W 70 links
4" Blk Oak S 20 E 78 links

No Date County Surveyor's Record Book 1, page 211, notes a stone at the corner.

1942 MN/DOT notes show corner was assumed at 4-way road intersection.

1948 MN/DOT road alignment map for TH 95 shows the corner at the centerline of a roads north/south & east/west. The corner is 10.7 feet south of new centerline and 57.9 feet east of the PI on tangent.

1999 James Nielsen, LS 11865, (MN/DOT) found nothing at the corner and set a cast iron monument 10.7 feet south of centerline based on highway stationing. He filed a Certificate of Location (#261571).

1999 James Kramer, LS 23668, (MN/DOT) found a 12" long 2" X 2" wood hub. He replaced it with a cast iron monument. He filed a Certificate of Location (#264147). This Certificate was to correct #261571.

2004 County Coordinates to CIM from traverse information by SEPI:
NAD 83 (1996 Adjustment)
N- 110574.751
E- 505541.002
Position fits 1948 centerline tie being 10.37 feet south of tangent and 57.04 feet east of PI.

2009 Westwood Professional Services, Inc. found a CIM recessed below the bituminous surface in the position given by James Kramer in 1999. A PK nail with Benton County washer was placed over the CIM and reference ties by Kramer were verified and two new ties were made.

County Coordinates Obtained by GPS:
NAD 83 (1996 Adjustment)
N- 110574.771
E- 505541.283