

**Statement of Evidence:**

**L332**

Northeast Corner of Section 33, Township 36 North, Range 30 West, Minden Township,  
4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey established this corner and set a wood post at this location and bearing trees were recorded.

6" Burr Oak	N 65 1/2 E	677 links
6" Blk. Oak	N 21 1/2 W	471 links

Pre 1940 MN/DOT notes by C. H. West for TH 95 show corner assumed at intersection of fences east, west, and south.

1980 William Lunser, LS 9394, set a 1/2" iron monument at the intersection of very old fences from the east and south. This was verified by measurements to the section corners 1 mile north and 1 mile east. He established reference ties. A Certificate of Location (#158856) was recorded.

1992 County Coordinates from MN/DOT:  
NAD 83 (1986 Adjustment)  
N-105443.288  
E-495003.736

1995 Comstock and Davis performed GPS work under contract with Benton County and Coordinates Obtained by GPS NAD 83 (1986 Adjustment) to a 1/2 " iron pipe:  
N- 105443.835  
E- 495003.870

2001 On October 31, 2001 Westwood Professional Services, Inc. found a 1/2" iron monument at the intersection of fence lines (mostly down) from the south and from the east. We found blazes in the trees that may be from Mr. Lunser's tree ties. We removed the 1/2" iron monument and set a cast iron monument at the location and established new ties.

2003 County Coordinates Obtained by Sidetie  
NAD 83 (1996 Adjustment)  
N- 105443.970  
E- 495003.300

2008 Westwood Professional Services, Inc. found a CIM, established new reference ties and verified the 2003 coordinates.