

Statement of Evidence:

L342

Northeast Corner of Section 34, Township 36 North, Range 30 West, Minden Township,
4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey established this corner and set a wood post at this location and bearing trees were recorded.

8" Bur Oak	S 16 1/4 W	563 links
8" Bur Oak	N 44 W	371 links

1977 Paul Wellen, LS 10461, found a 1/2" pipe at the corner location and filed a Certificate of Location (#147249).

1992 County Coordinates from MN/DOT to 3/4" iron pin:

NAD 83 (1986 Adjustment)
N-105370.768
E-500329.926

1995 County ties show found a 3/4" pin at the corner.

Comstock and Davis performed GPS work under contract with Benton County and Coordinates Obtained by GPS NAD 83 (1986 Adjustment) to a 1/2 " iron pin:
N- 105371.033
E- 500329.888

2003 Westwood Professional Services, Inc. found corner marked by a cast iron monument. Do not know who set the CIM, but it agrees with Wellen's position and the coordinates determined by Comstock and Davis.

County Coordinates by GPS to a found CIM.

NAD 83 (1996 Adjustment)
N- 105371.091
E- 500329.340

2008 Westwood Professional Services, Inc. verified the 2003 coordinates, established reference ties and placed a PK nail and county washer flush with bituminous surface over existing CIM.