

Statement of Evidence:

L352

Northeast Corner of Section 35, Township 36 North, Range 30 West, Minden Township,
4th Principal Meridian, Benton County, Minnesota.

1852 Original US General Land Office survey established this corner and set a wood post at this location and bearing trees were recorded.

14" Tamarack	S 7 1/2 E	21 links
5" Tamarack	N 51 W	15 links

Undated County Surveyor's Record Book 1, page 229, notes a Tamarack stake by the East corner Gate post.

1977 Paul Wollen, LS 10461, set a 1/2" iron pipe at the intersection of a fence lines east/west/north/south. He filed a Certificate of Location (#147250).

1995 Comstock and Davis performed GPS work under contract with Benton County and Coordinates Obtained by GPS NAD 83 (1986 Adjustment) to a CIM:

N- 105288.283
E- 505647.432

2000 Bogart & Pederson report the Benton County Coordinate position of the corner is +/-4.6 feet west and +/-1.7 feet north of the pipe as set by Wollen.

County Coordinates from Bogart & Pederson (**For Informational Purposes Only! – NOT VERIFIED**)

NAD83 (1986 Adjustment)
N – 105288.370
E – 505647.077

2004 County Coordinates by SEPI traverse:

NAD 83 (1996 Adjustment)
N- 105288.21
E- 505646.62