

Statement of Evidence:

L345

South Quarter Corner of Section 34, Township 36 North, Range 30 West, Minden Township, 4th Principal Meridian, Benton County, Minnesota.

1849 Original US General Land Office survey set a wood post in a mound at this location.

1969 Delbert Rieke, LS 5094, reestablished this corner at the split and on line between section corners and set a cast iron monument. A Sherburne County Certificate of Location (#112152) was made. Corner is shown 5 feet west of fence running south and 9 feet south of east-west fence line.

1993 Sherburne County Surveyor's Office found CIM and updated ties.

2002 No resurvey information was found on this corner in the Benton County records.

County Coordinates converted from Sherburne County Coordinates
NAD83 (1986 Adjustment)
N – 100012.36
E – 497783.43

NOTE: **These coordinates indicate that the corner is 28.3 feet south of a straight line between section corners and 3.8 west of the split. Need to check with Sherburne County.**

2004 Found CIM and measured 2654.26 feet to the SE corner and 2647.38 feet to the SW corner. CIM is 28.39 feet south of a straight line between section corners. County Coordinates obtained by GPS to CIM:
NAD83 (1986 Adjustment)
N - 100012.614
E - 497783.311

Sherburne County Surveyor plans to reset corner at the lost position.

2009 Westwood Professional Services, Inc. found CIM in position reported in 2004. Corner location needs to be examined and verified with the Sherburne county surveyor.