

Statement of Evidence:

I143

East Quarter Corner of Section 14, Township 37 North, Range 28 West, Maywood Township, 4th Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey established this corner and set a wood post and bearing trees were recorded as follows:

18" Elm	S 48 E	10 links
6" Ironwood	S 71 W	34 links

1932 County Engineer's Notebook No. 80 for survey of SAR 9 running south to north. Corner is shown in center of road with town road west and fence line east. Stationing gives distance of 2650.7 feet to the SE corner. Ties:

Guy P.	NE	39.7'
TP	E	30.9'

1961 County Engineer's Notebook No. 234 contains survey for CSAH 9 running south to north on section line. Notes show corner marked by an iron with town road west and fence line east. Same ties as listed below in 1962. Stationing gives distances of 2651.6 feet to the SE corner and 2669.6 feet to the NE corner with a no angle (POT).

1962 County Surveyor's Record Book 2, page 412, notes an iron was placed with the following reference ties (ties dated 1963).

Anchor Pole	SW	52.35
PP	NW	47.8
Anchor Pole	NE	49.8

Undated ties:

PP	NW	45.85
TP	NE	43.0
Anchor Pole	SW	45.3

2003 Westwood Professional Services, Inc. found ½ " iron pin in center of north-south road 9.28 feet south of the lost position. Accepted iron as marking the obliterated corner position. Measured 2651.46 feet to the SE corner Section 14.
County Coordinates obtained by GPS
NAD 83 (1996 Adjustment)
N- 151167.950
E- 568468.846