

Statement of Evidence:

I103

East Quarter Corner of Section 10, Township 37 North, Range 28 West, Maywood Township, 4th Principal Meridian, Benton County, Minnesota.

- 1855 Original US General Land Office survey established this corner and set a wood post for the corner and bearing trees were recorded.
- | | | |
|------------|--------|----------|
| 14" W. Ash | N 43 E | 21 links |
| 13" Elm | S 11 W | 26 links |
- 1902 County Surveyor's Record Book 2, page 406, and Record Book A, Map No. 31, contain a survey by John E. Whilt of Section 11, which shows a distance of 40.34 chains (2662.44 feet) to the Center of Sec 11.
- 1913 County Surveyor Record Book, pages 44 to 47, contains a survey in Section 10 by J. A. Stanton. Survey shows found stake and iron set by former County Surveyor.
- No Date County Surveyor's Record Book 2, on page 44, notes a distance of 2653 feet to the center of Sec 10.
- 2000 Scott Gyllen, LS 23003, Westwood Professional Services, Inc. set a ½ " iron pipe in the intersection of township roads north, east, and west for the obliterated position of the corner.
- 2001 Information from David Regan, LS 12236, shows he used iron pipe.
- 2003 Westwood Professional Services, Inc. found the iron pipe and measured 2667.96 feet to the center of section 11.
County Coordinates obtained by GPS
NAD 83 (1996 Adjustment)
N- 156314.450
E- 563125.871