

**Statement of Evidence:**

**I033**

East Quarter Corner of Section 3, Township 37 North, Range 28 West, Maywood Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

- 1855 Original US General Land Office survey established this corner and set a wood post for the corner and bearing trees were recorded.
- |              |        |          |
|--------------|--------|----------|
| 12" Tamarack | S 45 E | 9 links  |
| 10" Tamarack | N 35 W | 11 links |
- 1915 County Surveyor's Record Book 2, pages 314 and 315, show J. P. Soderstrum did a survey of Section 3. The survey is also noted in Record Book A, Map No. 9, and shows a stake set at the lost position with a distance of 41.98 chains to the SE corner of Sec. 3 and a distance of 40.06 chains to the NE corner Sec 3.
- 2003 Westwood Professional Services, Inc. measured 5411.33 feet between the Northeast and Southeast corners of Section 3, which compared well with Soderstrum's distance of 82.04 chains (5414.64 feet).
- 2006 Benton County Surveyor's Office set a steel T-post at the lost position between the Northeast and Southeast corners of Section 3. The overall distance between the Northeast and Southeast corners measured 5411.16 feet, which compares well with Westwood's distance. The distance to the Southeast corner is 2768.90 (41.95 chains) and the distance to the Northeast corner is 2642.26 feet (40.03 chains) compare well with the County Surveyor's record in 1915. Corner falls on the northwest side of a four way fence intersection

County Coordinates  
NAD 83 (1996 Adjustment)  
N-161735.702  
E-563078.399