

**Statement of Evidence:**

**I332**

Northeast Corner of Section 33, Township 37 North, Range 28 West, Maywood Township, 4<sup>th</sup> Principal Meridian, Benton County, Minnesota.

1855 Original US General Land Office survey set a wood post at this location and bearing trees were recorded.

10" Elm	S 50 W	16 links
15" Blk Ash	S 40 E	12 links

1902 County Surveyor's Record Book A, Map No. 38 shows a survey of Section 27 by John Whilt. Corner is shown as a post.

Note in County Surveyor's Record Book 2, page 438:

3 ½ link diameter stone S35 ½ W 33 links.

1925 County Engineer's notebook No. 45 lists ties to a wooden stake:

6" Willow	SE	37.8'
8" Oak	NW	77.5'

Gives distance of 5232.5 to the SE corner of Section 33.

1926 County Engineer's notebook No. 49 gives ties:

T.P.	NE	45.5'
T.P.	SE	46.4'

1940's County Engineer's Notebook No. 160 contains road survey for SAR No. 4 running west to east along the section line. Corner is shown as an iron pipe in center of road intersection with SAR No. 7 north-south. Ties:

TP	NE	41.4'
PP	SW	44.0'
TP	SE	133.5'

1971 County Surveyor's Record Book 2, page 450, gives ties to an iron:

Top West end apron	NW	69.0
Top Tel. Ped	NE	69.85
PP	SW	57.2

(Notation in Notebook No. 160 gives same ties to found iron.)

1993 Sidney Williamson, LS 10918, found a 1" solid iron pin and replaced it with a CIM. Filed Certificate of Location (No. 227423). Statement indicates that is was the same iron as found by Benton County Highway Department in the 1960's.

2003 County Coordinates computed from traverse information furnished by Surveying & Engineering Professionals, Inc.

NAD 83 (1996 Adjustment)

N- 137793.455

E- 558090.102